

SERIES 760

VANDAL-RESISTANT



Application

- Public areas
- High abuse lighting
- Locker rooms
- Stairwells
- Corridors
- Wall or Ceiling
- Bathrooms

Finish

- White

Features

- 16-gauge body and ends
- Tapped holes which accommodate tamper-resistant screws

Lens Options

- .125" Clear Polycarbonate lens
tamper and impact resistant - standard.
- .125 100% DR clear prismatic lens

Optional Features

- Battery backup: Holes for test switch, indicator light and emergency ballast
- CFL

Custom modifications in the physical specification and color are available for this fixture.

Lamping Options



T12	T8	T5	CFL
(1 or 2) 20W	(1 or 2) 17W	-	(1 or 2) 36W*
(1 or 2) 30W	(1 or 2) 25W	-	(1 or 2) 40W*
(1 or 2) 40W	(1 or 2) 32W	-	
		-	
		-	
		-	
		-	

* special order


Packaging	17W	20W	25W	30W	32W	40W
Bodies	12	12	12	12	12	12
Diffusers	48	48	24	24	24	24




SERIES 760




END



LENS



TOP



SIDE W/LENS

T8	
SIZE	LENGTH
(1 or 2) 17W	24-1/4
(1 or 2) 25W	36-1/4
(1 or 2) 32W	48-1/4

T12	
SIZE	LENGTH
(1 or 2) 20W	24-1/4
(1 or 2) 30W	36-1/4
(1 or 2) 40W	48-1/4

REV 3-1-05

