


SERIES 886

LINEAR WALL MOUNT

SLOTTED



Application

- Wall mount indirect luminaire with forward throw optics
- Sconce applications for hospitality, rest rooms, corridors and small offices
- Slotted openings accept Light Control Film from Lexalite, an ALP Company
- Openings could accept graphics for direction and location
- 2 ft and 3 ft versions are stand alone "sconces"

Finishes

- Housing: unpainted/unfinished formed steel housing in slotted patterns
- Customer to source local powder coating facilities for housing and die cast aluminum end caps

Reflector (optional):

- Enhanced forward throw aluminum
- Also available in white forward throw steel

Features

- Units are shipped with die cast aluminum joiners installed for structural continuity and for attaching other units for continual runs or end caps.
- The units mount to a wall bracket that compensates for uneven surfaces and allows for recessed electrical boxes. The brackets are 25 1/2"; 37 1/2" or 48 3/4" and two of the 48 3/4" brackets are required for the eight foot housing.
- A computer designed optical system maximizes the output of the (2) T8 or (2) T5 lamps (Series 856) producing minimal back light and maximum forward throw.
- Ballast mounting assembly allows for easy installation separate from housing and then installs with two fasteners.
- Architectural die cast chamfered aluminum ends are available for a complete designer look without exposed fasteners.

Optional Features

Custom modifications in the physical specification are available for a complete designer look. Check with the factory for motion/sound sensors.

Lamping Options

T8
(2) 17W (2')
(2) 25W (3')
(2) 32W (4')
(4) 32W (8')

Check with factory for LED and LED/fluorescent applications.

Packaging

	4'	8'
Bodies per skid	50	50




SERIES 886

LINEAR WALL MOUNT

SLOTTED


4-FOOT MODEL




8-FOOT MODEL

4-FOOT MODEL
WITH END CAPS


TOP VIEW



FRONT VIEW




2-11/16



END VIEW

8-FOOT MODEL
WITH END CAPS

TOP VIEW



FRONT VIEW




T8

SIZE	LENGTH
(2) 17W	25-3/4
(2) 25W	37-3/4
(2) 32W	49-1/4
(4) 32W	98

REV 1-30-09



PAINTING PROCEDURES FOR SUSPENDED & WALL MOUNT LINEAR FIXTURES



SEND THESE PROCEDURES WITH FIXTURES TO THE PAINTER

PROCEDURES:

1. Make sure end caps are mounted to the body before painting.
2. If no end caps are needed, make sure you mask off the outside face of the joiner before painting. This will assure a good fit between joiners.
3. Make sure the painter is aware that the body is steel and the end cap and joiner are aluminum cast.
4. The painter should check the gap between the end cap and joiner to make sure there is a good fit and that there are no gaps before painting. Close gaps by pushing the end cap towards the body.